Feature-augmented model for multilingual discourse relation classification

Eleni Metheniti, Chloé Braud, Philippe Muller

UT3 - IRIT - CNRS

firstname.lastname@irit.fr











DISRPT

DISRPT Shared Task: Discourse Relation Classification across Formalisms

IMPLICIT

ENG.PDTB.PDTB (wsj_2315)

Unit 1: RJR moved 11 employees of the group back to New

York in September

Unit 2: <u>because</u> "there was supposed to be a future."

DIRECTION: 1<2

Original Label: Contingency.Cause.Reason

DISRPT Label: Contingency.Cause

ENG.RST.RSTDT (wsj_1317)

Unit 1: Known as a traditional executive,

Unit 2: he is very much in the conservative American Express

mold.

Direction: 1>2

Original Label: elaboration-additional-e

DISRPT Label: elaboration

DISRPT 2021

- <u>DISRPT 2021 Shared Task</u>: Discourse Relation Classification across Formalisms
- 16 datasets, 11 languages, 3 frameworks
- <u>DisCoDisCo</u> (Gessler et al., 2021)

IMPLICIT

ENG.PDTB.PDTB (wsj_2315)

Unit 1: RJR moved 11 employees of the group back to New

York in September

Unit 2: because "there was supposed to be a future."

DIRECTION: 1<2

Original Label: Contingency.Cause.Reason

DISRPT Label: Contingency.Cause

ENG.RST.RSTDT (wsj_1317)

Unit 1: Known as a traditional executive,

Unit 2: he is very much in the conservative American Express mold.

DIRECTION: 1>2

Original Label: elaboration-additional-e

DISRPT Label: elaboration

DisCoDisCo system

Monolingual, one-per-corpus classifiers based on BERT

DisCoDisCo system

- Monolingual, one-per-corpus classifiers based on BERT
- **Features** in embedding layer (not the same for each classifier!):
 - Categorical features: genre, head word's POS, list of common words...
 - Numerical features: length of unit, position of unit in document, distance...
 - Boolean features: *same speaker, (unit) is sentence, (unit) is discontinuous*

DisCoDisCo system

- Monolingual, one-per-corpus classifiers based on BERT
- **Features** in embedding layer (not the same for each classifier!):
 - Categorical features: genre, head word's POS, list of common words...
 - Numerical features: length of unit, position of unit in document, distance...
 - Boolean features: same speaker, (unit) is sentence, (unit) is discontinuous
- Direction annotation with special tokens:

```
[CLS] } unit 1 > unit 2
```

[CLS] unit 1 < unit 2 {</pre>

DISRPT 2023

• <u>DISRPT 2023</u>: 26 datasets, 13 languages, 4 frameworks

DISRPT 2023

- <u>DISRPT 2023</u>: 26 datasets, 13 languages, 4 frameworks
- HITS (Liu et al., 2023): monolingual or framework-based, large models
- DiscReT (Metheniti et al., 2023): multilingual only, label harmonization,
 switching units for direction
- JiscoFLAN (Anuranjana, 2023): generative models, prediction filtering

Our research questions

Which DisCoDisCo features are best?

- All features
- "Common" features

Our research questions

Which DisCoDisCo features are best?

- All features
- "Common" features
- New features:
 Language, Framework, Corpus (LCF)

```
[French, SDRT, fra.sdrt.annodis]
[English, RST, eng.rst.rstdt]
```

Our research questions

Which DisCoDisCo features are best?

- All features
- "Common" features
- New features:
 Language, Framework, Corpus (LCF)

```
[French, SDRT, fra.sdrt.annodis]
[English, RST, eng.rst.rstdt]
```

How to handle relation direction best?

- No change
- DisCoDisCo direction special tokens
- DiscReT switching units

- Multilingual, multi-framework joint setting for DISRPT 2021
- Pretrained models: mBERT, DistilmBERT, XLM-RoBERTa (all in base size)

- **Multilingual**, **multi-framework** joint setting for DISRPT 2021
- Pretrained models: mBERT, DistilmBERT, XLM-RoBERTa (all in base size)
- **Features**: added to vocabulary, before units. Input:

```
[CLS] language corpus framework feature _{\rm length} feature _{\rm POS-Unit\_1} ... feature _{\rm percent} This is Unit 1 , [SEP] then follows Unit 2 .
```

- Multilingual, multi-framework joint setting for DISRPT 2021
- Pretrained models: mBERT, DistilmBERT, XLM-RoBERTa (all in base size)
- **Features**: added to vocabulary, before units. Input:

```
[CLS] language corpus framework feature _{\rm length} feature _{\rm POS-Unit\_1} ... feature _{\rm percent} This is Unit 1 , [SEP] then follows Unit 2 .
```

Direction: see DisCoDisCo, DiscReT

- **Multilingual**, **multi-framework** joint setting for DISRPT 2021
- Pretrained models: mBERT, DistilmBERT, XLM-RoBERTa (all in base size)
- **Features**: added to vocabulary, before units. Input:

```
[CLS] language corpus framework feature _{\rm length} feature _{\rm POS-Unit\_1} ... feature _{\rm percent} This is Unit 1 , [SEP] then follows Unit 2 .
```

- Direction: see DisCoDisCo, DiscReT
- **Label filtering**: based on framework, not corpus

```
PDTB:{ expansion.conjunction: 0.2, joint: 0.25, contingency.cause: 0.02 ...}
```

Results

Model:	DisCoDisCo 2021	mBERT	DistilmBERT	XLM-R	mBERT	DistilmBERT	XLM-R
Direction:	Add. tokens	Add. tokens			Switching units		
No features	60.41	59.54	56.81	62.09	58.36	55.69	60.52
Common features	61.82	62.56	60.92	64.86	59.75	57.24	61.14
All features	-	63.09	60.28	64.50	62.33	59.08	63.95
LCF	-	61.76	59.17	64.13	58.34	55.69	60.52
LCF + Common	-	63.46	62.01	65.91	61.12	57.75	62.88
LCF + All	-	63.67	61.92	65.53	63.89	59.65	63.51

Results

Model:	DisCoDisCo 2021	mBERT	DistilmBERT	XLM-R	mBERT	DistilmBERT	XLM-R
Direction:	Add. tokens	Add. tokens			Switching units		
No features	60.41	59.54	56.81	62.09	58.36	55.69	60.52
Common features	61.82	62.56	60.92	64.86	59.75	57.24	61.14
All features	-	63.09	60.28	64.50	62.33	59.08	63.95
LCF	-	61.76	59.17	64.13	58.34	55.69	60.52
LCF + Common	-	63.46	62.01	65.91	61.12	57.75	62.88
LCF + All	-	63.67	61.92	65.53	63.89	59.65	63.51

Results: Features

- Best overall:
 - <u>LCF + Common</u> for XLM-R, DistilmBERT
 - LCF + All for mBERT
- +4% accuracy compared to DisCoDisCo (62% -> 66%)

- Big improvement for spa.rst.sctb (+16%) and deu.rst.pcc (+10%)
- 3-8% improvement on the rest...
- ...but no improvement on eus.rst.ert

Results: Direction

• Overall: Using direction information > Not using it

Without features: Additional tokens > Switching units > None (for all models)

• With features: **Additional tokens** for XLM-R and DistilmBERT

Switching units for mBERT

Conclusion

1. Multilingual discourse relation classification can be better than monolingual!

2. Features work well for all models and languages!

3. Direction information is useful! Additional tokens over other manipulation

Thank you for your attention!

Find the project on GitLab:

gitlab.irit.fr/melodi/andiamo/relation-classification-features

